



## 52mm L.E.D. 360 DEGREE LIGHTS 3.5" POLE WITH ANGLE BRACKET



### SPECIFICATIONS

LED: 52mm diameter in red, yellow, green blue and white, 3.5 inch pole length, 16 inch pig tail wire, single contact bayonet base

Use: Indicator Lamp

Intensity: 75mcd or greater

WIRING DIAGRAMS ON BACK PAGE

Continuous Only ←

Flashing/Continuous Capable ←

VOLTAGE	COLOR	F/C	PART #	\$ PER
24VDC	R	Cont.	LD-5221-100	60.00
24VDC	R/G	Cont.	LD-5222-100	85.00
24VDC	R/Y/G	Cont.	LD-5223-100	97.00
24VDC	R/Y/G/B	Cont.	LD-5224-100	130.00
24VDC	R/Y/G/B/W	Cont.	LD-5225-100	150.00
24VDC	R	Flash	LD-5221-101	60.00
24VDC	R/G	Flash	LD-5222-101	85.00
24VDC	R/Y/G	Flash	LD-5223-101	97.00
24VDC	R/Y/G/B	Flash	LD-5224-101	130.00
24VDC	R/Y/G/B/W	Flash	LD-5225-101	150.00
120VAC	R	Cont.	LD-5211-100	60.00
120VAC	R/G	Cont.	LD-5212-100	85.00
120VAC	R/Y/G	Cont.	LD-5213-100	97.00
120VAC	R/Y/G/B	Cont.	LD-5214-100	130.00
120VAC	R/Y/G/B/W	Cont.	LD-5215-100	150.00
120VAC	R	Flash	LD-5211-101	60.00
120VAC	R/G	Flash	LD-5212-101	85.00
120VAC	R/Y/G	Flash	LD-5213-101	97.00
120VAC	R/Y/G/B	Flash	LD-5214-101	130.00
120VAC	R/Y/G/B/W	Flash	LD-5215-101	150.00

Pricing subject to change.

American LED-gible Inc.

1776 Lone Eagle Street Columbus, Ohio 43228

Phone: 614-851-1100 Fax: 614-851-1121

### WHAT MAKES US DIFFERENT?



Have a broken light? No problem. With our LED stack lights you can replace the bulb and not the entire stack.

Do you need two red, yellow, green, blue or white in a single stack? No problem. With a simple lens and bulb change you have it. MAX. 5 lights per stack of any color R/Y/G/B/W.

### COMMON USES

- ✓ MATERIAL, QUALITY, SUPERVISOR CALLS
- ✓ LINE STOPPAGE, ASSISTANCE NEEDED
- ✓ MACHINE STATUS
- ✓ PREDICTIVE AND PREVENTATIVE MAINTENANCE



MISC. ACCESSORIES	PART #	\$ PER
10 INCH POLE	LD-2782-100	5.00
SURFACE MOUNT BASE	LD-5200-101	10.00

**\*All stack light units include one wall mount angle bracket, 3.5" pole and LED bulbs and lens.** Optional adder for 10" pole or surface mount base see above. Customer responsible for changing to larger pole and extending cable length as needed. Each light stack comes with approx. 16 inch pig tail cable.

### SPARE PARTS



SPARE PARTS	PART #	\$ PER
ANGLE BRACKET	LD-5200-100	4.95
PLASTIC LENS RED	GP-2782-002	5.95
PLASTIC LENS YELLOW	GP-2782-004	5.95
PLASTIC LENS GREEN	GP-2782-005	5.95
PLASTIC LENS BLUE	GP-2782-006	5.95
PLASTIC LENS WHITE	GP-2782-009	5.95

**LIGHT TYPES: 24VAC/DC CONTINUOUS,  
24VAC/DC FLASH CAPABLE,  
120VAC FLASH CAPABLE  
USE 24VAC/DC BULB TYPE**

VOLTAGE	COLOR	F/C	BULB #	\$ PER
24VDC	RED	F/C	LD-2782-102	9.95
24VDC	YELLOW	F/C	LD-2782-104	9.95
24VDC	GREEN	F/C	LD-2782-105	9.95
24VDC	BLUE	F/C	LD-2782-106	9.95
24VDC	WHITE	F/C	LD-2782-109	9.95

**LIGHT TYPES: 120VAC CONTINUOUS  
USES 120VAC BULB TYPE**

VOLTAGE	COLOR	F/C	BULB #	\$ PER
120VAC	RED	Cont.	LD-2782-112	9.95
120VAC	YELLOW	Cont.	LD-2782-114	9.95
120VAC	GREEN	Cont.	LD-2782-115	9.95
120VAC	BLUE	Cont.	LD-2782-116	9.95
120VAC	WHITE	Cont.	LD-2782-119	9.95

Phone: 614-851-1100

www.ledgible.com

www.ledandon.com